

VÝPIS VÝZTUŽE STROPU NAD 1.NP

POL.	Ø	TVAR	DL. (m)	KS	R6	R8	R10	R12	R16	Ø8- -150/150	Ø6- -150/150
1	R12		6,15	86				528,9			
2	R10		4,20	86			361,2				
3	R12		7,00	42				294,0			
4	R12		8,20	36				295,2			
5	R10		6,10	114			695,4				
6	R8		6,10	112		683,2					
7	R10		3,00	21			63,0				
8	R10		3,80	15			57,0				
9	R8		1,00	20		20,0					
10	R8		3,00	10		30,0					
11	R10		4,10	9			36,9				
12	R10		2,00	9			18,0				
13	R8		1,30	34		44,2					
14	R10		2,70	9			24,3				
15	R10		4,70	9			42,3				
16	R10		1,20	18			21,6				
17	R10		6,00	30			180,0				
18	R12		4,80	160			768,0				
19	R12		3,60	17			61,2				
20	R8		2,20	231		508,2					
21	R8		2,90	20		58,0					
22	R8		6,00	120		720,0					
23	R10		1,40	20			28,0				
24	R6		1,26	32	40,3						
25	R6		0,84	30	25,2						
26	R12		3,80	4			15,2				
27	R6		0,84	21	17,6						
28	R12		1,20	4			4,80				
				bm	83,1	2063,6	1527,7	1967,3			
				ks	kg	19,0	815,0	943,0	1746,0		

OCEL:10 505(R) CELKEM KG=3523,0